# aeroqual 88

## **INDOOR AIR QUALITY TEST KITS**



Indoor Starter Kit

### Portable and accurate real-time air quality information, made affordable

Easy-to-use air quality monitoring kits with everything required to get started measuring common indoor pollutants, or for checking compliance to the WELL Building Standard™ (WELL).

Expand the kits at any time from our wide range of sensor heads for different gases, or customize a kit to suit your requirements.

Can also be used outdoors.



Indoor Pro Kit

Kit for WELL

### Kits at a glance

KIT / CONTENTS	SERIES 500 MONITOR*	SENSORS						
		PM	CO <sub>2</sub>	VOC	СО	O <sub>3</sub>	Temp / RH	CARRY CASE
Starter Kit	✓	✓	✓	GSS			✓	Small
Pro Kit	✓	✓	✓	PID	✓		✓	Large
Kit for WELL	✓	✓			✓	<b>√</b>	✓	Small

<sup>\*</sup>Series 500 Monitor base including: LCD digital display, Lithium battery and charger, in-built datalogger, monitor to USB cable, PC software.

#### Who are they for?

- Health and safety managers who need to demonstrate safe environments
- Researchers who want to collect scientifically robust data on a limited budget
- Air quality professionals who need real-time measurements
- Educators who want students to learn about air pollution in a way that supports STEM

#### What are they for?

- Indoor air quality assessments
- Personal exposure checks
- Health and safety compliance
- Health and comfort assessment
- Checking indoor air pollution "hotspots"
- HVAC system performance monitoring
- Indoor air quality studies
- WELL Compliance assessments

### **Specifications I Indoor Air Quality Test Kits**

#### **Sensor specifications**

GAS & PARTICULATE RANG SENSORS	PANGE	SENSOR TYPE*	MINIMUM DETECTION LIMIT	ACCURACY OF FACTORY CALIBRATION	RESOLUTION	RESPONSE TIME	TEMPERATURE	RELATIVE HUMIDITY	KIT		
	NANGE								STR	PRO	WELL
Particulate Matter (PM <sub>10</sub> & PM <sub>2.5</sub> )	0.000 to 1.000 mg/m <sup>3</sup>	LPC	0.001 mg/m <sup>3</sup>	± (0.002 mg/m³ + 15 % of reading)	0.001 mg/m <sup>3</sup>	5 Seconds	0 to 40°C	0 to 90 %	✓	✓	✓
Ozone (O <sub>3</sub> )	0-0.5 ppm	GSS	0.001 ppm	<±0.008 ppm 0-0.1 ppm <±10% 0.1-0.5 ppm	0.001 ppm	60 Seconds	0 to 40°C	10 to 90 %			✓
Carbon Dioxide (CO <sub>2</sub> )	0-5000 ppm	NDIR	20 ppm	<±20 ppm + 5%	1 ppm	120 Seconds	0 to 40°C	15 to 90 %	✓	✓	
Carbon Monoxide (CO)	0-100 ppm	GSE	0.2 ppm	<±1 ppm 0-10 ppm <±1 10% 10-100 ppm	0.01 ppm	30 Seconds	0 to 40°C	15 to 90 %		<b>✓</b>	✓
VOC	0-25 ppm	GSS	0.1 ppm	<±0.1 ppm + 10%	0.1 ppm	60 Seconds	0 to 40 °C	15 to 90 %	✓		
VOC	0-20 ppm	PID	0.01 ppm	<±0.2 ppm + 10%	0.01 ppm	30 Seconds	0 to 40°C	0 to 95 %		✓	

<sup>\*</sup> Sensor Types: Gas Sensitive Semiconductor (GSS), Gas Sensitive Electrochemical (GSE), Laser Particle Counter (LPC), Non-dispersive infrared (NDIR), Photoionization Detector (PID).

For the full range of available sensors, visit our website;  $\underline{www.aeroqual.com} \text{ or to download the list, click } \underline{here}.$ 

#### **Monitor specifications**

SERIES 500 PORTABLE MONITOR SYSTEM SPECIFICATIONS (included in Starter & Pro Air Testing Kits)				
Measurement units	Gas: ppm or mg/m³   Humidity: %   Temperature °C or F			
Reading functions	Instant, minimum, maximum, average			
Sensor head	Active fan sampling to ensure high accuracy measurements, interchangeable, replaceable			
Display status indicators	Battery, sensor, standby			
Sensor calibration	Zero and gain calibration in the lab or field			
Analog output	0-5 V			
Digital interface	RS-232 to USB			
Data logging	Up to 8,188 records (2,706 incl. Temp/RH)			
PC data logging	Software and data cable supplied. Link data to a specific location and monitor.			
Clock function	Real time			
Power supply	12V DC (power adaptor/charger supplied 100-250 V AC)			
Rechargeable battery	Lithium polymer 12 V DC 2700 mA/h			
Enclosure material and rating	PC and ABS; IP20 and NEMA 1 equivalent			
Size	(L x W x D) 195 x 122 x 54 (mm); 7% x 4% x 2% (in) (with sensor head)			
Weight	< 460 g; < 16 oz (with sensor head and battery)			
Environmental operating conditions	Temperature: -5 °C to 45 °C   Humidity: 0 to 95 % non-condensing			
Temperature & Humidity sensor	Range - 40 °C to 124 °C (- 40 °F to 255 °F); Range 0 to 100 % RH			
Approvals	Part 15 of FCC Rules; EN 50082-1: 1997; EN 50081-1: 1992			





### **WWW.HOSKIN.CA**

• ENVIRONMENTAL • INSTRUMENTATION • MATERIALS TESTING

• INTEGRATED SYSTEMS • RENTALS • SERVICE