

PV SERIES POCKET SCALES




APPLICATIONS

- Multiple Weighing Units (g / oz / dwt / ozt)
- Fast & Simple Calibration
- Standard Battery Operation
- Low Battery Indicator
- Auto Power Off to Conserve Battery Life
- Compact Size for Easy Portability
- Vinyl Carrying Case
- One Year Warranty

PV SERIES POCKET SCALES

Accuracy is the keystone of all measuring, monitoring and controlling applications.

The PV Series offers high performance at a low price. Perfect for thousands of applications:



- Gold/Silver/Gem Weighing
- Hobby Applications
- Education
- Manufacturing/ Production
- Inventory Management/ Stockroom
- Quality Control
- Packaging
- Sample Preparation
- Environmental Testing
- Paint, Ink & Chemical Mixing
- Portion Control and Dietary Management
- Field Testing
- Checkweighing
- Postal Scale

Specifications

	PV-100	PV-200	PV-500	PV-1000
Grams (g)	60 x 0.01	100x0.1	200x0.1	500 x 0.1
Decimal (oz)	21 x 0.001	35 x 0.005	7 x 0.005	17.5 x 0.005
Troy Ounce (ozt)	19 x 0.001	3 x 0.005	6 x 0.005	16 x 0.005
Pennyweight (dwt)	38x 0.01	77 x 0.1	128x0.1	320 x 0.1
Calibration Wt. (Standard)	so ± 0.005g	so ± 0.05g	100±0.05g	200 ± 0.05g
Repeatability/ Std. Dev.		± two display readability		
Linearity		± two display readability		
Sensitivity Drift		± 50 ppm / °C (10 °C ~ 35 °C / 50 °F ~ 95 °F)		
Stabilization Time		3 seconds (typically)		
Overload Indicator		EE		
Underload Indicator		-EE		
Auto Power Off		Within 10 minutes with no activity		
Operating Temperature		5 °C ~ 35 °C / 41 °F ~ 95 °F		
Display Type		5 Digits LCD		
Low Battery Indicator		c b		
Power Requirement		2 AAA size alkaline batteries (standard)		
Typical Battery Life		40 hours with alkaline batteries		
Pan Size		3.25" (W) x 3" (D)		
Dimensions		3" (W) x 5.3" (D) x 0.8" (H)		

Specifications subject to change without notice



WWW.HOSKIN.CA

- INTEGRATED SYSTEMS • RENTALS • SERVICE
- ENVIRONMENTAL • INSTRUMENTATION • MATERIALS TESTING

Vancouver | Burlington | Montréal | Edmonton