

ODO RTU

OPTICAL DISSOLVED OXYGEN & TEMPERATURE SENSOR

An easy way to install YSI ODO™ technology at your site, tank, or pond.

Engineered specifically for aquaculture applications, but at home in any Modbus system, the optical dissolved oxygen (ODO) sensor can be used to ensure adequate oxygen levels for your livestock or for improved energy efficiency. With YSI's **ODO RTU**, you'll benefit from reduced costs, less maintenance, and better data.

ODO RTU utilizes the most advanced DO technology and can be connected anywhere without the need for special connectors. Additional inputs for barometric pressure and salinity are used to accurately calculate the DO% and mg/L. ODO RTU is also available with built-in conductivity measurement to automatically compensate for salinity.



Connect directly to your PLC or data logger and communicate via Modbus



Highly-accurate ODO sensor technology with no stirring



2-year cable and probe warranty with user-replaceable DO cap



a xylem brand



ODO RTU OPTICAL DISSOLVED OXYGEN & TEMPERATURE SENSOR

ODO RTU



Size

ODO RTU Specifications (ODO/T probe assembly)	
	2.46 cm diameter, Cable options for 1, 4, 10, 20, 30, 50, and 100 m lengths
Dissolved Oxygen (Optical luminescence) Units: % saturation, % saturation local, mg/L, ppm	Range 0 to 500%, 0 to 50 mg/L Accuracy 0 to 200%: ±1% of reading or 1% saturation, whichever is greater; 200 to 500%: ±8% of reading; 0 to 20 mg/L: ±0.1 mg/L or 1% of reading, whichever is greater; 20 to 50 mg/L: ±8% of reading
Temperature (Thermistor)	Resolution 0.01 mg/L and 0.1 %, or 0.1 mg/L and 1% (auto-adjusted based on range)
Units: °C, °F, K	Range -5 to 70°C (-5 to 50°C; DO compensation range for mg/L) Accuracy ±0.2°C Resolution 0.1°C or 0.1°F (auto-adjusted based on range)
Communication	Modbus/RS485 (4 wire)
Default Baud Rate	9600 (user programmable)
Power Requirements	10 V to 16 V DC, 15 mA max
	2 years on cable, probe, and ODO sensor cap
Additional Conductivity Specifications (ODO/CT probe assembly)	
Conductivity (Four nickel electrode cell) Units: µS/cm, mS/cm	Range 0 to 200 mS/cm Accuracy 0 to 100 mS/cm ±0.5% of reading or 0.001 mS/cm, whichever is greater; 100 to 200 mS/cm ±1.0% of reading Resolution 0.001, 0.01, or 0.1 µS (range dependent)
Salinity (See YSI.com for additional calculated parameters) Units: ppt, mS/cm	Range 0 to 70 ppt Accuracy ±1.0% of reading or ±0.1 ppt, whichever is greater Resolution 0.01 ppt
Part Numbers	
627180	ODO RTU Probe Assembly cable lengths available in 1, 4, 10, 20, 30, 50, and 100m options
627180	ODO RTU Probe Assembly with Conductivity cable lengths available in 1, 4, 10, 20, 30, 50, and 100m options
	Replacement ODO Extended Warranty Sensor Cap

SPECIFICATIONS XA00138



WWW.HOSKIN.CA

- ENVIRONMENTAL • INSTRUMENTATION • MATERIALS TESTING
- INTEGRATED SYSTEMS • RENTALS • SERVICE

Vancouver | Oakville | Montréal | Edmonton